



**ELECTRICAL**

	Voltage	4-20mA	CAN
Supply Voltage	+5 to +32VDC*	+9 to +32VDC	+5 to +32VDC
Over Voltage Protection	>32 VDC		
Power Consumption	<0.7 W	<2.6 W	<0.7 W
Reverse Polarity Protection	to -32 VDC		
Analog Resolution	10 bit		
Report Rate	10 Hz	1 Hz	
Sensor Configuration	Accessible via USB		

\* Supply voltage to be minimum 0.5V above output voltage

**ANALOG OUTPUTS**

	Voltage	4-20mA
Channel 1 (fine)	0 – 10 VDC (configurable)	1 mA – 20 mA (configurable)
Channel 2 (Coarse)	0 – 10 VDC (configurable)	1 mA – 20 mA (configurable)
Channel 3 (Oil/Temp)	0 – 10 VDC (configurable)	1 mA – 20 mA (configurable)
Error Indication	0 – 10 VDC (configurable)	1 mA – 20 mA (configurable)
Optional Output Inhibit (during zero/span)	0 – 10 VDC (configurable)	1 mA – 20 mA (configurable)

**CONNECTIONS**

Sensor Wiring	26 AWG PTFE 3G210 Shielded with DR-25 Jacket
Armor	Optional

**CHEMICAL COMPATIBILITY**

Fuels	Diesel, Gasoline
Oils	Hydraulic, Gear, Mineral, Vegetable, Synthetic Ester, Semi-synthetic, Polyalphaolefin (PAO), Polyalkyleneglycol (PAG)
Coolants	Ethylene Glycol, water
Fluids	Salt water
Differential Pressure	10 Bar
Cable Pull	3 axis, 50 N
General Handling	1m Within Packaging on all 3 sides

**MECHANICAL**

Sensor Size	57mm x ø24.5mm
Junction Box	105.5mm x 105.5mm x 66mm
Sensor Mounting	2 off M6 Socket Cap Screws (not supplied)
Weight	0.70kg
Materials (sensor)	Aluminum Alloy, FEP, PEI
Materials (Junction box)	Aluminum Alloy, st/steel, polyester

**DIGITAL OUTPUTS**

J1939 Data length	8 bytes
PGN	130816
Byte 0	Coarse measurement Value in range 0 – 100
Byte 1	Fine measurement percentage, no scaling Value 255 – optional output inhibited during calibration
Byte 2	8 Status bits
Bit 0	High/Low temperature exceeded
Bit 1	Oil Upper threshold exceeded
Bit 2	Oil Lower threshold exceeded
Bit 3	Fine measurement error
Bit 4	Coarse measurement error
Bit 5	Oil measurement error
Bit 6	Internal temperature sensor error
Bit 7	External temperature sensor error
Byte 3-7	Manufacturer use

**ENVIRONMENTAL**

Protection Class Sensor:	IP68 / IP69k to EN60529	
Enclosure	IP65 to EN60529	
Operating temp	Sensor	-40°C to +150°C to EN60945, EN60068-2-1, ISO16750-4
	Enclosure	-40°C to +85°C to EN60945, EN60068-2-1, ISO16750-4
Humidity	95% RH +55°C EN60945, EN60068-2-30 Test Db, ISO16750-4	
Thermal Shock	EN60945, EN60068-2-14 Test Na, ISO16750-4	

**EMC**

Marine	EN60945
Vehicle Components	EN 50498 & Automotive E-marking to UN ECE Reg 10
Light Industrial	EN61000-6-3, EN61000-6-1
Heavy Industrial	EN61000-6-4, EN61000-6-2
Measurement Control	EN61326-2-1
Construction Machinery	EN13309
Earth Moving Machinery	ISO 13766
Agricultural & Forest Machinery	ISO 14982

**VIBRATION**

Marine EN60945	3 axis 2 to 13Hz, +/-1mm 13.2Hz to 100Hz constant acceleration of 0.7g
Industrial EN60068-2-6	3 Axis 10 to 55 Hz 0.75mm or 10g
Motorsport / Automotive	3 Axis Random 5 - 2000 Hz Up to 36g
Shock EN60068-2-27	3 Axis 25g, 6ms, 1000 cycles

## Connections

### 4-20 mA & 0-10V

	WHITE	FINE
	GREEN	COARSE
	ORANGE	OIL/TEMP
	BLACK	PWR GROUND
	RED	POWER
	BLUE	(NOT CONNECTED)
	SPARE	SHIELD

### CAN

	WHITE	CAN H
	BLUE	CAN L
	ORANGE	(NOT CONNECTED)
	GREEN	(NOT CONNECTED)
	RED	POWER
	BLACK	GROUND
	SPARE	SHIELD


## Part Numbers

<b>IN-LINE OIL DEBRIS ASSY</b> 4-20 mA	<b>SI-900-048</b>
<b>IN-LINE OIL DEBRIS ASSY</b> VOLTAGE	<b>SI-900-049</b>
<b>IN-LINE OIL DEBRIS ASSY</b> CAN	<b>SI-900-050</b>
<b>USB CABLE</b>	<b>1000-CO-116</b>
<b>USB STICK</b>	<b>1000-SW-001</b>

## Configuration Software

Each **SI-900 Industrial Oil Condition Transmitter Kit** includes companion PC software; the software is used to:

- Initially configure the monitor
- Compliment the monitors external indicators with an integral software alarm panel
- Updating of the monitor's alarm settings and re-configuration post 3<sup>rd</sup> party oil sample testing
- Periodically review archived oil condition data and trends



**ALARM PANEL**



**RECORD / TREND**

### Spectrum Instruments Ltd.

44 Forest Drive,  
Brighton, On K0K 1H0  
Canada

Tel: 1-613-439-8767  
Fax: 1-866-782-0106  
info@spectrum-  
instruments.com

LOCAL AUTHORIZED DISTRIBUTOR