

# MZ-3634-01

## Outdoor Megapixel Manual Zoom IP-Camera

- 2 Megapixel resolution
- Day/Night switching for almost any lighting condition
- H.264, MPEG4, MJPEG
- PoE compliant
- Stainless Steel Enclosure rated IP-68



The MZ-3634-01 is a high-quality, high-resolution color video camera with a vari-focal lens and auto-iris. The lens provided is adjustable from 3 to 8 mm, to provide a horizontal field-of-view of over 90 degrees. Other lens options are available. The MZ-3634-01 supports multiple codecs and is able to deliver H.264, MPEG4, and MJPEG video.

The camera can accept one contact closure or TTL input from an auxiliary security or process-monitoring device to initiate automatic views and video recordings of intrusions or process malfunctions.

The camera is housed in a heavy duty, all weather, stainless steel, IP-68 rated enclosure ready for mounting and requires only a powered Ethernet network connection.

# IVC MZ-3634-01

<b>Imager</b>	1/3.2" CMOS
<b>Shutter</b>	1/5 - 1/40,000 seconds
<b>Min. Illum.</b>	0.1 Lux
<b>Exposure</b>	Auto
<b>White Balance</b>	Auto
<b>Iris</b>	Auto
<b>Focus</b>	Manual
<b>View Angle</b>	35.2° - 90.7°
<b>Focal Length</b>	3 - 8 mm
<b>F-number</b>	1.2
<b>Ethernet</b>	100Base-TX/10BaseT (RJ-45)
<b>I/O Terminals</b>	1 Input, 1 Output
<b>Alarms</b>	In-video; tamper
<b>Resolution</b>	1600 x 1200 pixels
<b>Compression</b>	M-JPEG, MPEG-4, H.264
<b>Frame Rate</b>	30 FPS (1280 x 720) 15 FPS (1600 x 1200)
<b>Protocols</b>	TCP/IP, HTTP, FTP, SMTP
<b>Weight</b>	24 lbs.
<b>Voltage Req.</b>	12 VDC, 24 VAC, IEEE 802.3af PoE, 110-240 VAC
<b>Power Cons.</b>	28 W Max
<b>Oper. Temp</b>	-29° to 50° C
<b>Dimensions</b>	6.1" W x 4.57" H
<b>Mount</b>	Wall
<b>Rating</b>	IP-68



1080p High Definition broadcast quality image



30 Frames Per Second in 720p HD for smooth video



Multiple power options available, including Power over Ethernet (PoE)



Rated IP-68 for continuous immersion in water

## IVC Camera Management Software

Point & click camera management & control



Robust, enterprise class software to manage and control your cameras and video from anywhere in the world.

### Ordering Information:

MZ-3634-01-Fn-V

V	Voltage Required
	12D 12 VDC
	24A 24 VAC
	115 110-120 VAC
	220 220-240 VAC
	POE 802.3af POE
-Fn	Connection Type
	1 10/100 RJ-45

### Accessories:

**MB-100** Pole Mount Kit



330 Nevada Street  
Newton, MA 02460  
ph: 617-467-3059  
fax: 617-687-0751  
email: sales@ivcco.com