

MZ-3634-01

Outdoor Megapixel Manual Zoom IP-Camera

- 2 Megapixel resolution
- Day/Night switching for almost any lighting condition
- H.264, MPEG4, MJPEG
- PoE compliant
- Stainless Steel Enclosure rated IP-68



The MZ-3634-01 is a high-quality, high-resolution color video camera with a vari-focal lens and auto-iris. The lens provided is adjustable from 3 to 8 mm, to provide a horizontal field-of-view of over 90 degrees. Other lens options are available. The MZ-3634-01 supports multiple codecs and is able to deliver H.264, MPEG4, and MJPEG video.

The camera can accept one contact closure or TTL input from an auxiliary security or process-monitoring device to initiate automatic views and video recordings of intrusions or process malfunctions.


The camera is housed in a heavy duty, all weather, stainless steel, IP-68 rated enclosure ready for mounting and requires only a powered Ethernet network connection.

IVC MZ-3634-01

Imager	1/3.2" CMOS
Shutter	1/5 - 1/40,000 seconds
Min. Illum.	0.1 Lux
Exposure	Auto
White Balance	Auto
Iris	Auto
Focus	Manual
View Angle	35.2° - 90.7°
Focal Length	3 - 8 mm
F-number	1.2
Ethernet	100Base-TX/10BaseT (RJ-45)
I/O Terminals	1 Input, 1 Output
Alarms	In-video; tamper
Resolution	1600 x 1200 pixels
Compression	M-JPEG, MPEG-4, H.264
Frame Rate	30 FPS (1280 x 720) 15 FPS (1600 x 1200)
Protocols	TCP/IP, HTTP, FTP, SMTP
Weight	24 lbs.
Voltage Req.	12 VDC, 24 VAC, IEEE 802.3af PoE, 110-240 VAC
Power Cons.	28 W Max
Oper. Temp	-29° to 50° C
Dimensions	6.1" W x 4.57" H
Mount	Wall
Rating	IP-68



1080p High Definition broadcast quality image



30 Frames Per Second in 720p HD for smooth video



Multiple power options available, including Power over Ethernet (PoE)



Rated IP-68 for continuous immersion in water

IVC Camera Management Software

Point & click camera management & control



Robust, enterprise class software to manage and control your cameras and video from anywhere in the world.

Ordering Information:

MZ-3634-01-Fn-V

V	Voltage Required
	12D 12 VDC
	24A 24 VAC
	115 110-120 VAC
	220 220-240 VAC
	POE 802.3af POE
-Fn	Connection Type
	1 10/100 RJ-45

Accessories:

MB-100 Pole Mount Kit



330 Nevada Street
Newton, MA 02460
ph: 617-467-3059
fax: 617-687-0751
email: sales@ivcco.com