

PTZ-3330-04

Low-light, Outdoor Pan/Tilt/Zoom IP-Camera

- Cost-effective outdoor PTZ camera
- Day/Night switching for almost any lighting condition
- Suitable for harsh weather environments
- Local storage of 1000 frames



The PTZ-3330-04 is a high quality, high-resolution color video camera with outstanding low-light performance. It has an 36x motor-driven optical zoom and a 4x digital multiplier providing 144x total zoom. The pan, tilt, and zoom functions can be controlled automatically and precisely from anywhere using the click-to-point and preset view features of the IVC Relay Server Software. This PTZ camera is a high performance low-light camera that automatically switches to black and white and removes an IR cut filter to increase sensitivity in low light conditions.

The camera can accept four contact closures or TTL inputs from auxiliary security or process-monitoring devices to initiate automatic views and video recordings of intrusions or process malfunctions. The unit includes an IP module for local storage of approximately 1000 frames of pre- and post-event video at 320x240 resolution.

The camera is housed in a weatherproof dome with an automatic heater and blower. The camera is ready for mounting and requires only a power and network connection.


Imager	1/4" Sony ExView CCD
Shutter	1 to 1/10,000 seconds
Min. Illum.	0.7 Lux (Color); 0.01 Lux (B/W)
Exposure	Auto
White Balance	Auto
Iris	Auto
Focus	Auto and manual
View Angle	1.7° - 57.8°
Focal Length	3.4 - 122.4 mm
F-number	1.4
Zoom ratio	36x Optical; 4x Digital; 144x Total
Pan Angle	360°
Pan Speed	360° per second
Tilt Angle	-90° to 0° (113° view range)
Tilt Speed	360° per second
Ethernet	100Base-TX/10BaseT (RJ-45)
I/O Terminals	4 Inputs, 4 Outputs
Resolution	704 x 480
Compression	M-JPEG, MPEG-4
Frame Rate	30 FPS (M-JPEG); 21 FPS (MPEG-4)
Protocols	TCP/IP, HTTP, FTP, SMTP
Weight	17 lbs.
Voltage Req.	110 VAC
Power Cons.	45 W
Oper. Temp	-29° to 50° C
Dimensions	14"H x 11"D (Camera Enclosure) 15"L x 5.5"H x 4"W (Mount Arm)
Mount	Wall Mount Standard
Rating	IP-66




Outdoor Rated IP-66 all weather camera



30 Frames Per Second for smooth video



View one stream at low frame rate & resolution; store another at high frame rate & resolution



High Speed Pan/Tilt provides 360 degree rotation in under 1 second

IVC Camera Management Software

Point & click camera management & control



Robust, enterprise class software to manage and control your cameras and video from anywhere in the world.

Ordering Information:

PTZ-3330-04-Fn-V

V	Voltage Required
	110 110-120 VAC
-Fn	Connection Type
	1 10/100 RJ-45

Accessories:

MB-100 Pole Mount Kit



330 Nevada Street
Newton, MA 02460
ph: 617-467-3059
fax: 617-687-0751
email: sales@ivcco.com