PTZ-3330-15

Wireless, Outdoor Pan/Tilt/Zoom IP-Camera

- High power 802.11 b/g/n compatible radio
- Day/Night switching for almost any lighting condition
- Suitable for harsh weather environments
- 30 FPS

The PTZ-3330-15 is a high quality, high-resolution color video camera with outstanding low-light performance. It has an 18x motor-driven optical zoom and a 4x digital multiplier providing 72x total zoom. The pan, tilt, and zoom functions can be controlled automatically and precisely from anywhere using the click-to-point and preset view features of the IVC Relay Server Software. This PTZ camera is a high performance low-light camera that automatically switches to black and white and removes an IR cut filter to increase sensitivity in low light conditions.

The camera can accept one contact closure or TTL input from an auxiliary security or process-monitoring device to initiate automatic views and video recordings of intrusions or process malfunctions.

The camera is housed in a weatherproof dome with an automatic heater and blower. It includes an integrated, high-power 802.11b/g/n radio.

IVC PTZ-3330-15

Imager	1/4" Sony ExView CCD
Shutter	1 to 1/10,000 seconds
Min. Illum.	0.7 Lux (Color); 0.01 Lux (B/W)
Exposure	Auto
White Balance	Auto
Iris	Auto
Focus	Auto and manual
View Angle	2.8° - 48°
Focal Length	4.1 – 73.8 mm
F-number	1.4
Zoom ratio	18x Optical; 4x Digital; 72x Total
Pan Angle	360°
Pan Speed	360° per second
Tilt Angle	-90° to 0° (113° view range)
Tilt Speed	360° per second
Ethernet	Integrated 802.11b/g/n radio
I/O Terminals	1 Input, 1 Output
Resolution	704 x 480 and 352 x 240 pixels
Compression	M-JPEG, MPEG-4, H.264
Frame Rate	30 FPS
Protocols	TCP/IP, HTTP, FTP, SMTP
Weight	14 lbs.
Voltage Req.	24 VDC, 110 VAC
Power Cons.	50 W Max
Oper. Temp	-29° to 50° C
Dimensions	21.5" H x 10" W x 10" D
Mount	Wall or Pendant
Rating	IP-66

Integrated 802.11 b/g/n wireless radio.

H.264 Encoding transfers high quality video at a lower frame rate for seamless motion

High Speed Pan/Tilt provides 360 degree rotation in under 1 second

Outdoor rated IP-66 all weather camera

IVC Camera Management Software

Point & click camera management & control

Robust, enterprise class software to manage and control your cameras and video from anywhere in the world.

Ordering Information:

PTZ-3330-15-Fn-V

V	Voltage Required
24D	24 VDC
110	110 - 120 VAC

-Fn	Connection Type
G	802.11 b/g/n radio

Accessories:

MB-101 Pole Mount Kit

330 Nevada Street
Newton, MA 02460
ph: 617-467-3059
fax: 617-687-0751
email: sales@ivcco.com

© 2012, Industrial Video & Control Co. The Industrial Video & Control Co. logo is a registered trademark of Industrial Video & Control Co.. All other company names and products are trademarks or registered trademarks of their respective companies. All information provided is subject to change without notice.